



IVECO SPECIFICATIONS

Model	Daily 35S15V11/ E4	Daily 50C15V16/ E4	Daily 50C15V16/ E4 Sisonke 23 Seater	Daily 65C15V18 26 Seater Midibus	Daily 50C15V18/ E4	Daily 50C17V18 LD A8 V/E5	Daily 70C15V20/ E4	Daily 55S15WH 4x4	Daily 55S15WDH 4x4 Crew Cab	Daily 70C15/E4	Daily 70C15D/E4
DIMENSIONS (mm)											
Overall Length	5 650	7 230	7 230	7 630	7 630	7 630	7 630	5 432	5 432	7 373	7 373
Overall Width	2 010	2 010	2 010	2 174	2 010	2 010	2 052	2 016	2 016	2 052	2 052
Overall Height	2 580	2 700	2 700	2 700	2 745	2 700	3 050	2 634	2 667	2 187	2 115
Front Overhang	1 008	1 008	1 008	1 008	1 008	1 008	1 008	900	900	1 008	1 008
Rear Overhang	1 120	2 120	2 120	2 520	2 520	2 520	2 520	1 132	1 132	2 015	2 015
Wheel Base	3 520	4 100	4 100	4 100	4 100	4 100	4 100	3 400	3 400	4 350	4 350
Bumper to Back of Cab	N/A	N/A	N/A	N/A	N/A	N/A	N/A	2 516	3 188	2 375	3 128
Cab to Rear Axle/ Unit	N/A	N/A	N/A	N/A	N/A	N/A	N/A	1 784	1 112	2 983	2 230
Turning Diameter (m)	12,7	14,4	14,4	14,76	14,4	14,4	14,4	14,4	14,4	15,5	15,5
MASS DATA (kg)											
Manufacturer's Gross Vehicle Mass	3 600	5 400	5 400	6 500	5 400	5 400	7 000	5 500	5 500	7 200	7 200
Manufacturer's Gross Combination Mass	7 000	8 700	8 900	10 000	8 700	8 700	10 500	9 000	9 000	10 500	10 500
Manufacturer's Front Axle Mass	1 900	2 100	2 100	2 300	2 100	2 100	2 500	2 450	2 450	2 500	2 500
Manufacturer's Rear Axle Mass	2 240	3 700	3 700	5 000	3 700	3 700	5 350	3 700	3 700	5 350	5 350
Permissible Maximum Vehicle Mass	3 600	5 400	5 400	6 500	5 400	5 400	7 000	5 500	5 500	7 200	7 200
Permissible Maximum Front Axle Mass	1 900	2 100	2 100	2 300	2 100	2 100	2 500	2 450	2 450	2 500	2 500
Permissible Maximum Rear Axle Mass	2 240	3 700	3 700	5 000	3 700	3 700	5 350	3 700	3 700	5 350	5 350
Unladen Front Axle Mass	1 250	1 425	1 645	1 664	1 425	1 519	1 574	1 745	1 840	1 495	1 615
Unladen Rear Axle Mass	865	1 145	2 059	2 240	1 185	1 243	1 453	820	925	800	895
Total Unladen Mass	2 115	2 570	3 704	3 904	2 610	2 762	3 026	2 545	2 765	2 295	2 510
Permissible Maximum Drawing Vehicle Mass	7 000	8 700	8 900	10 000	8 700	8 700	10 500	9 000	9 000	10 500	10 500
ENGINE											
Make	IVECO	IVECO	IVECO	IVECO	IVECO	IVECO	IVECO	IVECO	IVECO	IVECO	IVECO
Model Configuration	F1C	F1C	F1C	F1C	F1C	F1C	F1C	F1C	F1C	F1C	F1C
Capacity (cm³)	3 000	3 000	3 000	3 000	3 000	3 000	3 000	3 000	3 000	3 000	3 000
Maximum Power (kW @ r/min)	107 @ 3 200 - 3 500	107 @ 3 200 - 3 500	107 @ 3 200 - 3 500	107 @ 3 200 - 3 500	107 @ 3 200 - 3 500	125 @ 3 000 - 3 500	107 @ 3 200 - 3 500	107 @ 3 200 - 3 500	107 @ 3 200 - 3 500	107 @ 3 200 - 3 500	107 @ 3 200 - 3 500
Maximum Torque (Nm @ r/min)	350 @ 1 400 - 2 600	350 @ 1 400 - 2 600	350 @ 1 400 - 2 600	350 @ 1 400 - 2 600	350 @ 1 400 - 2 600	400 @ 1 250 - 2 600	350 @ 1 400 - 2 600	350 @ 1 400 - 2 600	350 @ 1 400 - 2 600	350 @ 1 400 - 2 600	350 @ 1 400 - 2 600
Gearbox											
Make / Model	6S400 OD	6S400 OD	6S400 OD	6S400 OD	6S400 OD	8 Speed Hi-Matic	6S400 OD	6S400 OD	6S400 OD	6S400 OD	6S400 OD
Number of Gears	6	6	6	6	6	8	6	6	6	6	6
High and Low Ratios	5.37:1 / 0.79:1	5.37:1 / 0.79:1	5.37:1 / 0.79:1	5.37:1 / 0.79:1	5.37:1 / 0.79:1	4.69:1 / 0.667:1	5.37:1 / 0.79:1	5.37:1 / 0.79:1	5.37:1 / 0.79:1	5.37:1 / 0.79:1	5.37:1 / 0.79:1
Synchromesh or Constantmesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Auto	Synchromesh	Synchromesh	Synchromesh	Synchromesh	Synchromesh
Rear Axle Ratio	3.91:1	4.18:1	4.18:1	4.18:1	4.18:1	3.91:1	5.13:1	4.87:1	4.87:1	4.55:1	4.55:1
Retarder	Optional	Optional	Optional	Optional	Optional	Optional	Optional	N/A	N/A	Optional	Optional
STANDARD TYRE EQUIPMENT											
Size and Ply Rating	225/70 R15	195/75 R16	195/75 R16	195/75 R16	195/75 R16	195/75 R16	225/75 R16	255/100 R16	255/100 R16	225/75 R16	225/75 R16
Radial or Crossply	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial	Radial

